

T70 1

The classic for lifting applications



Characteristics

- High-sensitivity two-step push button.
- Multiband Radio with Full-Duplex communication.
- Highly customizable.
- LCD display.
- External removable EEPROM SIM module.
- Easy and fast maintenance.
- High resistance to impacts.
- Frequency management against interferences.

Specifications

Transmitter	T70 1
Stop Function	Cat. 3 - PLd.
Ingress Protection	IP65/NEMA4.
Anti condensation system	na.
Frequency Band	Multiband (400 - 930 MHz).
Main Mechanisms (Max. #)	Pushbutton (6).
Auxiliary Mechanisms	Toggle & Rotary switches.
Removable EEPROM	External.
Battery Model	BT06K.
Battery Life	10h.
Operating Temperature Range	-20C +70C (-4F +158F).
Weight (with Battery) Grams	460.
Harness	Hand Strap / Shoulder Strap.
Display	2x12 Char LCD.
Cable Connection	na.
Range Limiter	YES.
Associated Receivers	R70/MP10/MR06/MR11/RCANCE/MP08.

Associated Applications



HEADQUARTERS

IKUSI · Pº Miramón, 170 · 20014 Donostia-San Sebastián · SPAIN
 Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusiremotecontrol.com

IKUSI WORLDWIDE

AUSTRALIA · CHILE · COLOMBIA · FRANCE · GERMANY · MEXICO · SPAIN · UNITED ARAB EMIRATES · USA



Leading Brands of Spain Forum